

Tire Size	Service Description	UTQG	Load Range	Sidewall	Approved Rim Width	Measured Rim Width	Section Width	Overall Diameter	Tread Width	Max Load	Tread Depth
P175/70R13	82 S	440 A B	STD	BLK	4.5 - 6	5	6.89	22.68	4.9	1036	10
P185/70R13	85 S	440 A B	STD	BLK	4.5 - 6	5.5	7.4	23.23	5.1	1135	10
P185/75R14	0	440 A B	STD	WSW	4.5 - 6	5	7.2	24.8	4.6	1290	10
P195/75R14	0	440 A B	STD	WSW	5 - 6.5	5.5	7.6	25.4	4.9	1400	10
P205/75R14	95	440 A B	STD	WSW	5 - 7	5.5	7.95	25.95	5.1	1532	10.5
P215/75R14	98 S	440 A B	STD	WSW	5.5 - 7	6	8.4	26.55	5.4	1664	10.5
P175/70R14	84 S	440 A B	STD	BLK	4.5 - 6	5	6.89	23.18	4.9	1102	10
P185/70R14	87 S	440 A B	STD	BLK	4.5 - 6	5.5	7.4	24.23	5.1	1201	10
P195/70R14	90 S	440 A B	STD	BLK	5 - 6.5	6	7.8	24.78	5.4	1312	10
P205/70R14	93 S	440 A B	STD	BLK	5 - 7	6	8.11	25.28	5.6	1433	10
P215/70R14	96 S	440 A B	STD	WSW	5.5 - 7	6.5	8.58	25.78	5.9	1554	10
P175/65R14	81 S	440 A B	STD	BLK	5 - 6	5	6.85	22.9	5	1019	10
P185/65R14	85 S	440 A B	STD	BLK	5 - 6.5	5.5	7.35	23.35	5.35	1124	10
P205/75R15	97 S	440 A B	STD	WSW	5 - 7	5.5	8.03	26.98	5.1	1598	10.5
P215/75R15	100 S	440 A B	STD	WSW	5.5 - 7	6	8.4	27.55	5.4	1742	10.5

P225/75R15	102 S	440 A B	STD	WSW	6 - 7.5	6	8.7	28.05	5.6	1874	10.5
P235/75R15	105 S	440 A B	STD	WSW	6 - 8	6.5	9.1	28.65	5.9	2028	11
P205/70R15	95 S	440 A B	STD	BLK	5 - 7	6	8.11	26.28	5.6	1499	10
P205/70R15	95 S	440 A B	STD	WSW	5 - 7	6	8.11	26.28	5.6	1499	10
P215/70R15	97 S	440 A B	STD	WSW	5.5 - 7	6.5	8.58	26.78	5.9	1620	10
P225/70R15	100 S	440 A B	STD	WSW	6 - 7.5	6.5	8.85	27.28	6.15	1753	10
P195/65R15	89 S	440 A B	STD	BLK	5.5 - 7	6	7.8	24.9	5.7	1279	10
P205/65R15	92 S	440 A B	STD	BLK	5.5 - 7.5	6	8.16	25.25	5.85	1400	10
P215/65R15	95 S	440 A B	STD	BLK	6 - 7.5	6.5	8.65	25.88	6.38	1510	10
P215/60R16	94 S	440 A B	STD	BLK	6 - 7.5	6.5	8.55	26.1	6.4	1477	10
P225/60R16	97 S	440 A B	STD	BLK	6 - 8	6.5	8.8	26.52	6.6	1609	10
P205/55R16	89 S	440 A B	STD	BLK	5.5 - 7.5	6.5	8.3	24.75	7.1	1279	10