

Tire Size	Service Description	UTQG	Load Range	Sidewall	Approved Rim Width	Measured Rim Width	Section Width	Overall Diameter	Tread Width	Max Load	Tread Depth
30X9.50R15LT	104 Q	0	C	OWL	6.5 - 8.5	7.5	9.63	29.35	7.4	1985	18
31X10.50R15LT	109 Q	0	C	OWL	7 - 9	8.5	10.71	30.47	8.2	2270	18
33X12.50R15LT	108 Q	0	C	OWL	8.5 - 11	10	12.36	32.63	9.8	2205	20
35X12.50R15LT	113 Q	0	C	OWL	8.5 - 11	10	12.87	34.88	10.2	2535	20
LT235/75R15	104 Q	0	C	OWL	6 - 7	6.5	9.14	28.62	7.2	1985	18
LT215/85R16	115 N	0	E	BLK	5.5 - 7	6	8.41	30.48	6.1	2680	18
LT235/85R16	120 N	0	E	BLK	6 - 7	6.5	9.29	31.9	7	3042	18
LT255/85R16	119 N	0	D	OWL	6.5 - 8	7	10.04	33.21	7.2	3000	18
LT225/75R16	115 N	0	E	BLK	6 - 7	6	8.54	29.35	6.6	2680	18
LT245/75R16	120 N	0	E	BLK	6.5 - 7.5	7	9.76	30.53	7.45	3042	18
LT265/75R16	112 N	0	C	OWL	7 - 8	7.5	10.5	31.64	8.1	2470	18
LT265/75R16	123 N	0	E	OWL	7 - 8	7.5	10.59	31.76	8.1	3415	18
LT285/75R16	122 N	0	D	OWL	7.5 - 9	8	11.3	32.8	9.2	3305	20
LT315/75R16	121 N	0	D	OWL	8 - 10	8.5	12.87	34.6	10	3195	20
LT305/70R16	118 Q	0	D	OWL	8 - 9.5	9	12.29	32.81	10	2910	18
33X12.50R17LT	114 Q	0	D	OWL	8.5 - 11	10	12.36	32.63	9.8	2600	20
35X12.50R17LT	119 Q	0	D	OWL	8.5 - 11	10	12.87	34.88	10.2	3000	20
LT235/80R17	120 Q	0	E	OWL	6 - 8	6.5	9.4	31.85	7	3085	18
LT245/75R17	121 Q	0	E	OWL	6.5 - 8	7	9.59	31.75	7.67	3195	18
LT245/70R17	119 Q	0	E	OWL	6.5 - 8	7	10.07	30.45	7.45	3000	18
LT265/70R17	112 Q	0	C	OWL	7 - 8.5	8	10.71	31.65	8.4	2470	18
LT265/70R17	121 Q	0	E	OWL	7 - 8.5	8	11.03	31.65	8.4	3195	18
LT285/70R17	121 Q	0	D	OWL	7.5 - 9.5	8.5	11.35	32.8	9.1	3195	18

LT275/70R18	125 Q	0	E	OWL	7 - 9	8	10.95	33.3	8.8	3640	18
-------------	-------	---	---	-----	-------	---	-------	------	-----	------	----