

Tire Size	Service Description	UTQG	Load Range	Sidewall	Approved Rim Width	Measured Rim Width	Section Width	Overall Diameter	Tread Width	Max Load	Tread Depth
225/70R14	99 S	500 A B	STD	OWL	6 - 7	6.5	8.9	26.45	7.05	1709	12.5
215/75R15	100 S	500 A B	STD	OWL	5.5 - 7	6	8.4	27.6	6.4	1764	13.5
225/75R15	102 S	500 A B	STD	OWL	6 - 7	6	8.7	28.33	6.65	1874	13.5
235/75R15	105 S	500 A B	STD	OWL	6 - 7.5	6.5	9.23	28.9	7	2039	14
235/75R15	109 S	500 A B	XL	OWL	6 - 8	6.5	9.2	28.9	7	2271	14
265/75R15	112 S	500 A B	STD	OWL	7 - 8.5	7.5	10.5	30.69	8	2469	14.5
225/70R15	100 S	500 A B	STD	OWL	6 - 7.5	6.5	9	27.45	7.05	1764	12.5
235/70R15	103 S	500 A B	STD	OWL	6 - 8	7	9.45	27.99	7.4	1929	12.5
265/70R15	112 S	500 A B	STD	OWL	7 - 9	8	10.6	29.6	8.45	2469	14
225/75R16	104 S	500 A B	STD	OWL	6 - 7.5	6	8.71	29.25	6.65	1984	13.5
235/75R16	108 S	500 A B	STD	OWL	6 - 8	6.5	9.25	29.84	7	2205	14
245/75R16	111 S	500 A B	STD	OWL	6.5 - 7.5	7	9.65	30.52	7.4	2403	14
265/75R16	116 S	500 A B	STD	OWL	7 - 9	7.5	10.51	31.65	8	2756	14.5
225/70R16	103 S	500 A B	STD	OWL	6 - 7	6.5	8.9	28.4	7.05	1929	13.5
235/70R16	106 T	500 A B	STD	OWL	6 - 8	7	9.46	28.99	7.43	2094	14

245/70R16	107 S	500 A B	STD	OWL	6.5 - 8	7	9.79	29.59	7.7	2149	13.5
255/70R16	111 S	500 A B	STD	OWL	6.5 - 8.5	7.5	10.24	30.1	8	2403	14
265/70R16	112 T	500 A B	STD	OWL	7 - 9	8	10.9	30.45	8.45	2469	14
255/70R17	112 S	500 A B	STD	OWL	6.5 - 8.5	7.5	10.24	31.1	8	2469	14
265/70R17	115 S	500 A B	STD	OWL	7 - 9	8	10.7	31.6	8.45	2679	14
265/70R18	116 S	500 A B	STD	OWL	7 - 9	8	10.7	32.6	8.45	2756	14
265/65R18	114 T	500 A B	STD	OWL	7.5 - 9.5	8	10.52	31.5	8.86	2601	13.5
265/60R18	110 T	500 A B	STD	OWL	7.5 - 9.5	8	10.52	30.46	9.05	2337	13.5
275/55R20	117 S	500 A B	XL	OWL	7.5 - 9.5	8.5	11.18	31.92	9.4	2833	13