

Tire Size	Service Description	UTQG	Load Range	Sidewall	Approved Rim Width	Measured Rim Width	Section Width	Overall Diameter	Tread Width	Max Load	Tread Depth
175/70R13	82 T	540 A B	STD	BLK	4.5 - 6	5	6.89	22.68	5.1	1047	10
175/70R14	84 T	540 A B	STD	BLK	4.5 - 6	5	6.89	23.68	5.1	1102	10
185/70R14	88 T	540 A B	STD	BLK	4.5 - 6	5.5	7.4	24.23	5.3	1235	10
195/70R14	91 T	540 A B	STD	BLK	5 - 6.5	6	7.8	24.78	5.6	1356	10
205/70R14	95 T	540 A B	STD	WSW	5 - 7	6	8.11	25.28	5.8	1521	10.5
215/70R14	96 T	540 A B	STD	WSW	5.5 - 7	6.5	8.58	25.78	6.1	1565	10.5
175/65R14	82 T	540 A B	STD	BLK	5 - 6	5	6.85	22.95	5.2	1047	10
185/65R14	86 T	540 A B	STD	BLK	5 - 6.5	5.5	7.35	23.4	5.55	1168	10
205/70R15	96 T	540 A B	STD	WSW	5 - 7	6	8.11	26.18	5.8	1565	10.5
215/70R15	98 T	540 A B	STD	WSW	5.5 - 7	6.5	8.58	26.68	6.1	1653	10.5
185/65R15	88 T	540 A B	STD	BLK	5 - 6.5	5.5	7.35	24.4	5.55	1235	10
195/65R15	91 T	540 A B	STD	BLK	5.5 - 7	6	7.8	24.9	5.85	1356	10
205/65R15	94 T	540 A B	STD	BLK	5.5 - 7.5	6	8.16	25.26	6.05	1477	10.5
215/65R15	96 T	540 A B	STD	BLK	6 - 7.5	6.5	8.65	25.81	6.5	1565	10.5
185/60R15	84 T	540 A B	STD	BLK	5 - 6.5	5.5	7.18	23.59	5.62	1102	10

215/60R15	94 T	540 A B	STD	BLK	6 - 7.5	6.5	8.54	24.94	6.57	1477	10.5
215/65R16	98 T	540 A B	STD	BLK	6 - 7.5	6.5	8.65	26.81	6.5	1653	10.5
235/65R16	103 T	540 A B	STD	BLK	6.5 - 8.5	7	9.37	27.79	7.1	1929	10.5
215/60R16	95 T	540 A B	STD	BLK	6 - 7.5	6.5	8.55	25.93	6.55	1521	10.5
225/60R16	98 T	540 A B	STD	BLK	6 - 8	6.5	8.8	26.5	6.8	1653	10.5
205/55R16	91 T	540 A B	STD	BLK	5.5 - 7.5	6.5	8.3	24.64	7	1356	10
225/60R17	99 T	540 A B	STD	BLK	6 - 8	6.5	8.81	27.38	6.78	1709	10.5