

TYRE SIZE	TREAD PATTERN	PR	LI / SS	TYPE	RIM	TUBE / FLAP	TYRE DIMENSIONS (mm)					MIN.DUAL SPACING (mm)	LOAD CAPACITY (kg)		INFLATION (kPa)
							NEW		MAX. IN SERVICE		SR		LOAD WHEEL	STEERING WHEEL	
							OD	SW	OD	OW					
250-15*	FL-08	22	165A5	TT	8.00-15	300-15	840	300	857	324	-	345	6695	5150	1000
4.00-8	FL-01	8	94A5	TT	31/4I-8	4.00-8	414	115	422	124	188	138	870	670	900
4.00-8	FL-03	6	90A5	TT	3.00D-8	4.00-8	414	112	422	121	188	134	780	600	800
4.00-8	FL-03	6	90A5	TT	3.00D-8	4.00-8	414	112	422	121	188	134	780	600	800
4.00-8	FL-03	8	94A5	-	31/4I-8	4.00-8	414	115	422	124	188	138	870	670	900
4.00-8	FL-03	10	97A5	TT	31/4I-8	4.00-8	414	115	422	124	188	138	950	730	1000
4.00-8	FL-08	6	90A5	TT	3.00D-8	4.00-8	414	112	422	124	188	134	780	600	800
4.00-8	FL-08	6	90A5	-	3.00D-8	4.00-8	414	112	422	121	188	134	780	600	800
4.00-8	FL-08	8	94A5	TT	31/4I-8	4.00-8	414	115	422	124	188	138	870	670	900
4.00-8	FL-08	10	97A5	TT	31/4I-8	4.00-8	414	115	422	124	188	138	950	730	1000
5.00-8	FL-01	8	106A5	TT	3.00D-8	5.00-8	467	132	476	143	208	158	1235	950	825
5.00-8	FL-03	8	106A5	TT	3.00D-8	5.00-8	467	132	476	143	208	158	1235	950	825
5.00-8	FL-08	8	106A5	-	3.00D-8	5.00-8	467	132	476	143	208	158	1235	950	825
6.00-9	FL-01	10	118A5	TT	4.00E-9	6.00-9	540	160	551	173	240	192	1715	1320	850
6.00-9	FL-01	12	121A5	TT	4.00E-9	6.00-9	540	160	551	173	240	192	1885	1450	1000
6.00-9	FL-02	10	118A5	TT	4.00E-9	6.00-9	540	160	551	173	240	192	1715	1320	850
6.00-9	FL-02	12	121A5	-	4.00E-9	6.00-9	540	160	551	173	240	192	1885	1450	1000
6.00-9	FL-08	10	118A5	TT	4.00E-9	6.00-9	540	160	551	173	240	192	1715	1320	850
6.00-9	FL-08	12	121A5	TT	4.00E-9	6.00-9	540	160	551	173	240	192	1885	1450	1000
6.50-10	FL-01	10	122A5	TT	5.00F-10 (5.50F-10)	6.50-10	588	177	600	191	262	212 (218)	1950	1500	775
6.50-10	FL-01	12	125A5	TT	5.00F-10 (5.50F-10)	6.50-10	588	177	600	191	262	212 (218)	2145	1650	900
6.50-10	FL-02	10	122A5	TT	5.00F-10 (5.50F-10)	6.50-10	588	177	600	191	262	212 (218)	1950	1500	775
6.50-10	FL-02	12	125A5	TT	5.00F-10 (5.50F-10)	6.50-10	588	177	600	191	262	212 (218)	2145	1650	900
6.50-10	FL-08	10	122A5	TT	5.00F-10 (5.50F-10)	6.50-10	588	177	600	191	262	212 (218)	1950	1500	775
6.50-10	FL-08	12	125A5	TT	5.00F-10 (5.50F-10)	6.50-10	588	177	600	191	262	212 (218)	2145	1650	900
6.50-10	FL-08	14	128A5	TT	5.00F-10 (5.50F-10)	6.50-10	588	177	600	191	262	212 (218)	2340	1800	1000
7.00-12	FL-01	12	133A5	TT	5.00S-12	7.00-12	672	192	685	207	303	230	2680	2060	850
7.00-12	FL-01	14	134A5	TT	5.00S-12	7.00-12	672	192	685	207	303	230	2755	2120	900
7.00-12	FL-02	12	133A5	TT	5.00S-12	7.00-12	672	192	685	207	303	230	2680	2060	850
7.00-12	FL-02	14	134A5	TT	5.00S-12	7.00-12	672	192	685	207	303	230	2755	2120	900
7.00-12	FL-08	12	133A5	-	5.00S-12	7.00-12	672	192	685	207	303	230	2680	2060	850
7.00-12	FL-08	14	134A5	TT	5.00S-12	7.00-12	672	192	685	207	303	230	2755	2120	900
7.00-12	FL-08	14	143A5	TT	5.00S-12	7.00-12	672	192	685	207	303	230	3545	2725	700
7.00-12	FL-08	16	136A5	TT	5.00S-12	7.00-12	672	192	685	207	303	230	2910	2240	1000
7.50-15	FL-08	14	144A5	TT	6.0-15 (6.5-15)	7.50-15	772	212	787	229	350	254 (260)	2800	3640	925
7.50-15	FL-08	16	146A5	TT	6.0-15 (6.5-15)	7.50-15	772	212	787	229	350	254 (260)	3900	3000	1000
8.15-15	FL-04	14	146A5	TT	7.0-15	28x9-15	707	216	721	233	322	248	3900	3000	1000
8.15-15	FL-08	14	146A5	TT	7.0-15	28x9-15	707	216	721	233	322	248	3900	3000	1000
8.25-15	FL-06	14	149A5	TT	6.5-15	8.25-15	836	234	853	253	376	281	4225	3250	800
8.25-15	FL-08	18	153A5	-	6.5-15	8.25-15	836	234	853	253	376	281	4745	3650	1000
18x7-8	FL-08	8	111A5	TT	4.33R-8	18x7-8	462	173	471	187	206	199	1415	1090	700
18x7-8	FL-08	14	121A5	TT	4.33R-8	18x7-8	462	173	471	187	206	199	1885	1450	900
18x7-8	FL-08	16	125A5	TT	4.33R-8	18x7-8	462	173	471	187	206	199	2145	1650	1000
16x6-8	FL-08	16	113A5	-	4.33R-8	16x6-8	425	152	434	164	192	175	1495	1150	1000
23x5	FL-05	6	106B	TT	3.75P-13	23x5	635	155	654	167	295	186	-	950	600
23x5	FL-05	10	118B	TT	3.75P-13	23x5	635	155	654	167	295	186	-	1320	800
23x5	FL-07	6	113A5	TT	3.75P-13	23x5	635	155	654	167	290	186	1495	1150	525
23x5	FL-07	10	121A5	-	3.75P-13	23x5	635	155	654	167	290	186	1885	1450	800

TYRE SIZE	TREAD PATTERN	PR	LI / SS	TYPE	RIM	TUBE / FLAP	TYRE DIMENSIONS (mm)					MIN.DUAL SPACING (mm)	LOAD CAPACITY (kg)		INFLATION (kPa)
							NEW		MAX. IN SERVICE		SR		LOAD WHEEL	STEERING WHEEL	
							OD	SW	OD	OW					
23x9-10	FL-08*	20	142A5	TT	6.50F-10	23x9-10	595	225	607	243	260	259	3440	2650	1000
250/75-12	FL-08	14	143A5	TT	8.00G-12	250/75-12 (27x10-12)	681	261	697	275	314	293	3545	2725	700
250/75-12	FL-08	16	146A5	T	8.00G-12	250/75-12 (27x10-12)	681	261	697	274	314	293	3900	3000	800
250/75-12	FL-08	20	152A5	TT	8.00G-12	270/75-12 (27x10-12)	681	261	697	274	314	293	4615	3550	1000